Commercial Ultrasonic Gas Meter

All-electronic ultrasonic gas meter for small commercial users



Actual product appearance

CORE PARAMETERS

Meter Model
G6 - G40 (nominal flow 6/10/16/25/40 m³/h)

Start Flow
As low as 0.008 m³/h

Accuracy Class
1.5 (segmented correction up to 1.0)

Total Pressure Loss
≤ 250 Pa (G6) / ≤ 375 Pa (G10+)

Protection / Ex
IP65 / Ex ia IIB T3 Ga

Power Supply
Dry + lithium or dual lithium

Battery Life
Dry: ≥ 1 year | Lithium: ≥ 10 years

Communication
LoRa / NB-IoT / Cat1 remote; Infrared / Bluetooth near-field

Working Temperature
-25°C ~ +60°C

PRODUCT FEATURES

- All-electronic metering - no mechanical wear, accuracy does not degrade
- Segmented flow-coefficient correction for high accuracy
- Micro-leakage, constant-flow & abnormal large-flow monitoring
- Optional temperature & pressure compensation
- Optional pipeline pressure monitoring & detector linkage
- Prepayment & remote management supported

Standard Price	MOQ	Monthly Capacity	Lead Time
On request	**On request**	**On request**	**On request**

Specifications are subject to final selection data. Please contact our team for detailed drawings, dimensional tables, test reports and certificates. Commercial terms are confirmed in the formal quotation.

© SICHUAN YUANHENGDING TRADING CO., LTD.