# G6~G65 Series Commercial Diaphragm Gas Meter

Commercial metering, seven ratings to 100 m³/h



Actual product appearance

## CORE PARAMETERS

| | |
|---|---|
| METER MODEL<br>**G6 / G10 / G16 / G25 / G40 / G65** | ACCURACY CLASS<br>**Class 1.5** |
| QMAX (M³/H)<br>**10 / 16 / 25 / 40 / 65 / 100** | QMIN (M³/H)<br>**0.06 / 0.10 / 0.16 / 0.25 / 0.40 / 0.65** |
| MAX. WORKING PRESSURE<br>**30 kPa steel · 100 kPa cast-aluminium** | TOTAL PRESSURE LOSS<br>**≤200 Pa (G6) · ≤300 Pa (G10~G25) · ≤400 Pa (G65)** |
| WORKING TEMPERATURE<br>**-25 °C ~ +55 °C** | CONNECTION<br>**Threaded G1 1/4 ~ G3** |
| PROTECTION<br>**IP65** | REFERENCE STANDARD<br>**EN 1359 · OIML R31** |

## PRODUCT FEATURES

- Seven capacity ratings from G6 to G65, wide interchangeability
- Patented K-system error adjustment on the high-pressure type
- Steel-cased standard and cast-aluminium high-pressure types
- Temperature compensation available for G6T ~ G25T

| Standard Price | MOQ | Monthly Capacity | Lead Time |
|---|---|---|---|
| **On request** | **On request** | **On request** | **On request** |

Specifications are subject to final selection data. Please contact our team for detailed drawings, dimensional tables, test reports and certificates. Commercial terms are confirmed in the formal quotation.

© SICHUAN YUANHENGDING TRADING CO., LTD.