E/F Reducer

PN8 / PN16



- Up to 8 bar for gas; up to 16 bar for water
- International safe fusion voltage 39.5 V
- Optimum fusion parameters from bar code
- 4 mm pin connectors
- With fusion indicators
- With integral pipe fixation

TECHNICAL PARAMETERS

Nominal Size **dn25/20–dn63/50**	Pressure Rating **8 bar gas / 16 bar water**
Design **With integral pipe fixation**	Jointing Method **Electrofusion**
Medium **Gas / Water**	Working Temperature Range **—**
Body Material **PE**	Applicable Range **dn25/20–dn63/50**
Accessories **4 mm pin connectors, fusion indicators**	
Design Standard **GB15558.2 / GB/T13663.2 / EN1555.3 / EN12201.3 / ISO4437.3 / ISO4427.3**	

E/F REDUCER DIMENSIONS

d/d2 (mm)	GP	Weight (kg)	d1 (mm)	L (mm)	L1 (mm)	L2 (mm)
25/20	50	0.039	35	74	34	32
32/20	40	0.059	44	79	36	32
32/25	40	0.057	44	79	36	33
40/32	60	0.072	54	88	40	35
50/32	70	0.119	66	96	43	35
50/40	70	0.126	65	96	43	35
63/32	50	0.14	81	106	47	35
63/40	50	0.148	81	106	47	39
63/50	50	0.149	81	106	47	43
40/20	20	0.069	54	88	39	33
40/25	20	0.084	54	88	39	33

Common sizes shown; full range on request.