RTZ-50/0.4FQ Gas Pressure Regulator

Group Buildings & Small Commercial Regulation



Product appearance for reference

MAIN TECHNICAL PARAMETERS

Nominal Size (DN) **DN50**	Construction Type **Diaphragm-type direct-acting (valve body + main regulator + shut-off valve integrated)**
Max. Inlet Pressure **P1max=0.4 MPa**	Outlet Pressure Range **P2=1 ~5 KPa (low-pressure type); 5 ~15 KPa (medium-pressure type)**
Accuracy Class **δ up to ±5%**	Lock-up Pressure Class **Up to 1.1P2**
Operating Temperature **-20~60℃**	Connection Type
Applicable Medium **Natural gas, manufactured gas, LPG and other non-corrosive gases**	Safety Configuration **Automatic overpressure shut-off; overpressure safety relief (no relief for the medium-pressure type or when used with LPG)**

PRODUCT FEATURES

- Modular design
- Automatic overpressure shut-off
- Overpressure safety relief (no relief for the medium-pressure type or when used with LPG)
- Easy installation and maintenance

Flow Capacity

Flow table paste area

FLOW TABLE PASTE AREA

Paste the flow table from the official datasheet / catalogue

Standard Price	MOQ	Monthly Capacity	Lead Time
On request · Final quotation to prevail	**On request · Final quotation to prevail**	**On request · Final quotation to prevail**	**On request · Final quotation to prevail**

© SICHUAN YUANHENGDING TRADING CO., LTD. · This manual is for reference only